

DAILY TIME SWITCH, WITH BACK-UP TIME

1ROM1DR

- CLASS	II - EN60335 for correct connection only
- BURDEN	0.5W
- AUXILIARY POWER SUPPLY	from 220 to 240V \pm 10% - Frequency 50 Hz
- PRECISION	\pm 3sec/day at 22°C
- TEMPERATURE	working 0°C \div +50°C / storage -25°C \div +70°C
- MOVEMENT	Quartz
- BACK-UP TIME	100 h
- MINIMUM SETTING INTERVAL	15 min
- TERMINAL WIRES	2x2,5 mm ²
- PROTECTION DEGREE	IP20 - Sealable front cover
- SWITCHING CONTACT	16(4)A 250V AC
- DIMENSIONS / WEIGHT Kg.	1 DIN module / 0,08



Funzionamento: muovere i pins a destra (Off) o a sinistra (On), per stabilire quando il contatto 1-2 deve essere chiuso.

Operation: Move the pins to the right (Off) or the left(On), as per the needed times of connection on which the contact 1-2 will be closed.



Ruotare il disco sino a far corrispondere l'ora corrente sull'indice / Turn the dial till the index is on current time

Funzionamento a 2 posizioni / Manual operating switch 2 positions:

Automatico / Automatic

Permanente / Permanent (ON)

