



Klemsan®

270156 C1-SA

Voltage Monitoring Relay

General	Casing Width (mm)	17,5
	Connections	Screw Terminal
	Network	3Ø with Neutral
Phase Failure	Fixed Delay Time	500ms
Phase Sequence	Fixed Delay Time	500ms
Adjustable/Fixed Unbalanced Protection	Range/Limit	±5% - 20% arası
	Hysteresis	6.9VAC
	Delay Time	0.1 - 10 s
Adjustable Voltage Protection	Upper Limit	-
	Lower Limit	-
	Hysteresis	-
	Delay Time	-
Adjustable Current Protection	Upper Limit	-
	Lower Limit	-
	Hysteresis	-
	Delay Time	-
Adjustable Frequency Protection	Upper Limit	-
	Lower Limit	-
	Hysteresis	-
	Delay Time	-
Adjustable/Extremely High-Low Voltage Protection	Upper Limit	310VAC (L-N)
	Lower Limit	140VAC (L-N)
	Hysteresis	6VAC

	Delay Time	100ms
PTC Protection	Fixed Delay Time	-
	Threshold	-
General	Response Time for Monitoring Any Function	Maks. 250ms
	Type of Output	Relay
Auxiliary Contacts	Type	1 C/O (SPDT)
	Max. Ratings - AC (for NO Side)	5A/250V; 1250VA
	Max. Ratings - DC (for NO Side)	5A/30VDC; 150W
	Mechanical Lifetime	≥10 ⁷ operation
	Electrical Lifetime Operations (for NO Side)	5x10 ⁴ (5A@250VAC) 1x10 ⁵ (5A@30VDC)
Supply Voltage	DC	—
	AC	L1-N'den 85-320VAC
General	Supply Frequency	35-70Hz
	Control Input Voltage Range	—
Ambient Conditions	Operating Temperature	-20°C +60°C
	Storing Temperature	-40°C +75°C
	Relative Humidity (No Condensation)	Max. 95% (no condensation)
General	Operating Frequency	35-70Hz
	Protection Class	IP20
Power Consumption	DC	—
	AC	<3VA
General	Mounting Type	Panel or Rail
	EMC-EMI	✓
	Packing Unit	1
	Weight (g)	66
	Packing Unit	1
	Dimensions	—

Avrupa standartlarına uygunluk belgesi - CE Certificate

Order Info



Order Info
270156 Voltage Monitoring Relay

© 2022 Klemsan A.Ş.
www.klemsan.com