



Klemson®

270370 Z1-60S

General

Order Number	270370
Casing Width (mm)	17,5
Connections	Screw terminal
Functions	ND
Type of Output	Relay
Adjustment of Timing-1 & Timing-2	-
Lux Adjustment Rate	-
Sensitivity Adjustement Rate	-
Supply Frequency	50-60Hz
Trigger Input Voltage	-
Recovery Time	Max. 100msec
Protection Class	IP20
Weight (g)	60
Mounting Type	—
Schematics	—
Dimensions	—

Auxiliary Contacts

Type	1 C/O (SPDT)
Max. Ratings - AC (for NO side)	10A/250V; 1250 VA
Max. Ratings - DC (for NO side)	5A/30VDC; 150W
Mechanical Lifetime	≥ 10 ⁷
Electrical Lifetime Operations (for NO side)	"5×10 ⁴ (5A@250VAC) 1×10 ⁵ (5A@30VDC)"

Time Range

Timing-1	1sec=>60sec
----------	-------------

	Timing-2	-
Supply Voltage	DC	12VDC
	AC	12VAC or 180..265V AC
Ambient Conditions	Operating Temperature	-20 to +60 °C
	Storing Temperature	-40 to +75 °C
	Relative Humidity (No Condensation)	Max.95% (no condensation)
Power Consumption	DC	<1.25W
	AC	<2.5VA
EMC-EMI	55011/A1, 61000-4-2, 61000-4-3/A1, 61000-4-4, 61000-4-5, 61000-4-6, 61000-4-8, 61000-4-11	—
Liquid Level Electrode	Definition	On delay timer
	Order Number	270370
	Packing Units	1

Order Info

270370

© 2022 Klemsan A.Ş.
www.klemsan.com