



# Klemsan®

## 551017 KKC 6060

60x60 Slotted wiring duct,Grey

|                                    |                     |                |
|------------------------------------|---------------------|----------------|
| <b>General Product Information</b> | Insulating material | PVC - UL 94 V0 |
| <b>Operating Temperature</b>       | Minimum Temperature | -15°C          |
|                                    | Maximum Temperature | +60°C          |
| <b>Dimensions</b>                  | A                   | 60 mm          |
|                                    | B                   | 60 mm          |
|                                    | C                   | 13,8 mm        |
|                                    | D                   | 4 mm           |
|                                    | E                   | 6 mm           |
|                                    | F                   | 2,1 mm         |
|                                    | G                   | 4,5 mm         |
|                                    | H                   | 6,5 mm         |
|                                    | I                   | 25 mm          |
|                                    | <b>Length</b>       | U              |
| <b>Product Information</b>         | Packing Unit        | 12x2           |
|                                    | Working range       |                |



UL Sertifikası - UL Certificate

Alçak Gerilim direktiflerine uygunluk belgesi - VDE Certificate

Rusya Yangın Sertifikası - Rusya Yangın Sertifikası

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Avrupa standartlarına uygunluk belgesi - CE Certificate

Türk Standartlarına Uygunluk Belgesi - Wiring Duct TSE certificate

| Order Info |              | Dimensions                          |
|------------|--------------|-------------------------------------|
| ■          | 551017 60x60 | 60x60 Slotted wiring duct,Grey      |
| ■          | 551017WS     | 60x60 Wide slotted wiring duct,Grey |